



www.zgs.ag | info@zgs.ag

concerts & events







varioMat 2



i Technical specifications:

Material	High density polyethylene
Measurements	100 cm x 200 cm x 3,15 cm
Weight	40,5 kg / panel
Surface	profiled
Color	black
Weight load	approx. 130 to. (depending on substrate)
Transport	590 varioMAT 2 panels per truck

Ideal for:



windpower plant construction



road construction





line construction



concerts and events



Fields of application

The varioMAT 2 is a heavy-duty mat that can be laid by hand and withstands even the highest loads of 130 tons. It is suitable as a mobile construction road, crane parking space, temporary footpaths, for concerts, events and much more.

Characteristics

The newly designed profile with standardised ruts is suitable for driving over with a pallet truck or wheelbarrow. The varioMAT 2 is ideal for use on small construction sites, up to heavy-duty use of tracked vehicles and heavy construction machinery. Thus it offers application possibilities for events, construction and infrastructure. Two people can lay up to 60 varioMat 2 per hour without any additional aids

Logistics

For temporary use, our panels are easier to transport than most alternative road mats. This means that more floor mats can be loaded onto trucks or containers, reducing transport costs.

Service

We offer our products and services principally to you for rent from stock, for collection by yourself or including service, i. e. transport, assembly and dismantling according to plan as well as final cleaning. Also available for purchase on request. We would be pleased to provide you with a free, non-binding and individual offer.

